

# CONIFLOOR mat (G20)

## Prefabricated Rubber Granule Mat for Indoor Floorings

### Product description

CONIFLOOR mat (G20) is a pre-fabricated rubber granule mat bound with PUR binder made of black, recycled rubber

granules.

The mat is part of our indoor systems CONIFLOOR LPC +, CONIFLOOR LPC + fl and CONIFLOOR UPD +.

### Technical Data

<b>volumetric weight</b>	for all thicknesses	kg/m <sup>3</sup>	770
<b>tensile strength according to DIN 53 571</b>	for all thicknesses	N/mm <sup>2</sup>	approx. 0.6
<b>elongation at break</b>	for all thicknesses	%	approx. 60

*Above figures are guide values and should not be used as a base for specifications!*

### Application method

CONIFLOOR mat (G20) is delivered in rolls. Roll out the mat and cut according to needed length.

Then mat is rolled up again and adhesive (our CONIFLOOR 210) is applied on the floor for one web width. Roll the mat into the freshly applied adhesive.

All end and connecting pieces need to be held in place by weights. After about 30-60 minutes, the surface has to be rolled with a 50 kg roller in order to prevent the formation of blisters and areas of insufficient adhesion.

Details for the application of our CONIFLOOR 210 please find in the relevant technical data sheet. For further assistance please contact our Technical Service.

### Delivery

The mats are 1.50m wide and delivered in rolls. 4 rolls each are normally packed onto 1 pallet.

We offer the following thicknesses of the mats: 4mm and 6mm.

4mm rolls have a length of 30m and 6mm rolls have a length of 20m.

### Colour

black

### Storage

Store the rolls under dry conditions.