

# SMOOTHING AGENT

## Smoothing Agent for Granular Surfaces and Stone Carpets

### Product description

SMOOTHING AGENT is a very pure solvent.

well as SBR granules) / quartz minerals for sports surfaces, playgrounds and stone carpets.

### Fields of application

SMOOTHING AGENT simplifies the smoothing of fresh installed surfaces of binder and rubber granules (EPDM as

### Properties

SMOOTHING AGENT is a colourless, clear liquid with a comparatively high flash point. Compared to other products used for this purpose SMOOTHING AGENT is almost odourless.

### Technical Data

<b>Density</b>	at 23 °C	g/cm <sup>3</sup>	approx. 1.05
<b>Viscosity</b>	at 23 °C	mPas	approx. 2.6
<b>Flash point</b>		°C	86
<i>Above figures are guide values and must not be used as a base for specifications!</i>			

### Application method

SMOOTHING AGENT is filled into a pail or tub, so that the squeegees or trowels used during installation can be moistened.

The squeegee / trowel is dipped into the liquid, then the excess is stripped off in order to ensure an **economic** usage.

### Pack size

SMOOTHING AGENT is supplied in 5 kg or 25kg cans.

### Colour

colourless, clear

### Storage

Store in unopened cans under dry conditions at a temperature range of 5 - 25 °C.

Do not expose to direct sunlight.

Before use, please see "best before" date on the pail / drum.

### Safety precautions

For protective measures, transport regulations and waste management please refer to the Material Safety Data Sheet of the product.