

CONIPUR Mat (G30)

Prefabricated Rubber Granule Mat for Sports Flooring

Product description

CONIPUR Mat (G30) is a pre-fabricated rubber granule mat bound with PUR binder made of black, fine recycled rubber granules.

This mat is used as elastic layer under PUR coatings of sports and multipurpose halls where a force reduction according to EN 14904 is not required. Compared to our

other two types of elastic layers, CONIPUR Mat (G30) features the lowest force reduction.

To achieve the force reduction according to EN 14904 with a thickness of 6mm, we recommend our CONIPUR Mat (G31).

Technical Data

volumetric weight	for all thicknesses	kg/m ³	approx 720
ultimate tensile strength acc. to DIN 53 455	for all thicknesses	N/mm ²	> 0.6
<i>Above figures are guide values and must not be used as a base for specifications!</i>			

Application method

CONIPUR Mat (G30) is delivered in rolls. Roll out the mat and cut according to needed length. Then mat is rolled up again and adhesive (our CONIPUR 111) is applied on the floor for one web width. Roll the mat into the freshly applied adhesive.

After about 30-60 minutes, the surface has to be rolled with a 50 kg roller in order to prevent the formation of blisters and areas of insufficient adhesion.

Details for the application of our CONIPUR 111 please find in the relevant technical data sheet. For further assistance, please contact our Technical Service.

about the most commonly used mats. Further thicknesses upon request.

thickness in mm	width in m	roll length	kg/roll	m ² per roll
4	1.25	35	100.8	43.75
5	1.25	35	126.0	43.75
6	1.25	30	129.6	37.50
7	1.25	21	105.8	26.25
8	1.25	21	121.0	26.25

Delivery

The mats are 1.25 m wide and delivered in rolls normally packed onto pallets. Below you will find further details

Colour

black

Storage

Store the rolls under dry conditions.